



# VENETIAN

## ECO SOLVENT PRINTER

The Venetian Solvent Ink Printer has the ability to print in full color directly on CD, DVD, or Blu-ray media, without requiring the purchase of specially coated discs. It has a Continuous Ink System (CIS), which means no more replacement of expensive cartridges and reduces the overall cost per use. Incorporating 6-color printing technology means this printer produces stunning photo-quality images.



### SPECIAL FEATURES

- ≈ Low per item printing cost
- ≈ Glossy finish
- ≈ Water Proof and Scratch Proof
- ≈ Advanced MicroPiezo® inkjet printing technology
- ≈ Ink density control software included
- ≈ Strong Resolution with 6-color Eco solvent ink printing at up to 5760 dpi
- ≈ Bulk ink system with 100ml tanks
- ≈ Separate tank for waste ink collection
- ≈ Specially designed circulation system
- ≈ Optional ID Card printing, includes design template

Model Shown: VENSOL-100





Model Number	VENSOLPTR		VENSOL-100
Disc Capacity	1 disc		100 discs
Print Method	Solvent Inkjet		
Printing Technology	Ultra Hi-Definition printing Advanced MicroPiezo® 6 color printing technology		
Ink Palette	Black, Cyan, Light Cyan, Magenta, Light Magenta, and Yellow		
Ink Configuration	Continuous Ink System (CIS) with 100ml tanks Waste Ink tank included		
Ink Type	Eco Solvent		
Maximum Resolution (dots per inch)	5760 x 1440 optimized dpi		
Color Management	ICC Profiles		
Media Type (Disc Loader Mode)	N/A		Standard 120mm Blu-rays, CDs and DVDs
Media Type (Manual Mode)	Paper, Bond, Vinyl Standard 120mm Blu-rays, CDs and DVDs Mini discs (optional) ID Cards (optional)		
Minimum System Requirements for PC	CPU: Pentium 4, 2.4GHz RAM: 512MB 3 x Hi-Speed USB 2.0		
Operating Systems	Windows 7, Windows Vista, Windows XP		
Software Included	Printer driver Disc Design Software Ink Density Changer Software Pandora Auto-Printer Software		
Warranty	6 months parts & labor against manufacturer defect, excluding the Print Heads. 3 months on the Print Heads. Warranty excludes physical damage or defect due to neglect or deliberate damage caused by the user.		
Power Requirements	Rated voltage: 120 VAC Rated frequency: 50 - 60 Hz Rated current: 0.6 Amp 220~240V (upon request)		
Weight and Dimensions (W x D x H)	Dimension: 20 x 11 x 7.5 inches Weight: 16 lb		Dimension: 21 x 23.25 x 8.25 inches (19.50" H with input rods and output bin installed) Weight: 25 lb
Temperature	Operating: 50 ° to 95 °F (10 ° to 35 °C) Storage: -4 ° to 140 °F (-20 ° to 60 °C)		
Relative Humidity	Operating: 20 - 80% Storage: 5 - 85%"		
Safety Approvals	Safety standards UL60950-1, CSA C22.2 No. 60950-1 EMI FCC Part 15 subpart B class B CAN/CSA-CEI/IEC CISPR 22 class B		